



		60g/m <sup>2</sup>	70g/m <sup>2</sup>	75g/m <sup>2</sup>	80g/m <sup>2</sup>	90g/m <sup>2</sup>	100g/m <sup>2</sup>	110g/m <sup>2</sup>	120g/m <sup>2</sup>
<b>OFFSET</b>	Whiteness CIE	ISO 11475	161	161	161	161	161	161	161
	Opacity %	ISO 2471	87	91	92	94	95	96	97
	Moisture %	ISO 287	6,2	6,2	6,2	6,0	6,0	6,0	5,8
	Bendtsen Roughness ml/min	ISO 879/2	150	150	180	150	150	150	150
	Thickness µm	ISO 534	80	92	95	106	116	128	141
	Bulk µm <sup>3</sup> /g/m <sup>2</sup>	-	1,33	1,31	1,27	1,33	1,29	1,28	1,28

MAY 2016

Premium Offset Folio - Reels  
 Technical References - Targets only, without tolerances mentioned  
 Basis weight g/m<sup>2</sup> - ISO 534

**Additional Information about The Navigator Company, Mills and Products:**  
 The Navigator Company mills are chain-of-custody certified by NepCon  
 in accordance with FSC-STD-40-004  
 (INC-COC-001829) and FSC-STD-40-005 (INC-CW-001829).  
 In accordance with the requirements of ISO 9706 standard  
 Elemental Chlorine Free (ECF)  
 Quality Management Systems Standard ISO 9001  
 Environmental Management Systems Standard ISO 14001  
 Occupational Health and Safety Management Systems Standard OHSAS 18001



\* I valori espressi sono soggetti alle tolleranze stabilite dal produttore.

