

LENZA TOP RECYCLING



BASIS WEIGHT (g/m ²), ISO 536	70	80	90	100	115	135	150	170	190	250	300
THICKNESS (μm), ISO 534	90	100	113	125	145	165	185	210	235	300	360
OPACITY (%), ISO 2471	≥ 91	≥ 93	≥ 95	≥ 96	≥ 97	≥ 98					
ROUGHNESS BENDTSEN (SS) (ml/min), DIN 53108	160	160	160	160	160	160	160	160	190	160	160
PREPRINT		x	x	x							

QUALITY INFOS

- CIE Whiteness CIE ISO 11475: 90 %
- Whiteness ISO 2470: 80 %
- Bulk: 1,25 cm³/g
- Cobb 60: ≤30 g/m²
- Humidity rel. Offset: 45 %
- Humidity rel. Preprint: 35 %

PRODUCT FEATURES

- 100% recycled paper
- For laser and inkjet
- Excellent whiteness
- High opacity and cleanliness
- Excellent runability
- Ageing resistance
- DIN 6738: LDK 24-85
- Based on bioenergy and local sourcing
- Inhouse de-inking
- Closed loop; no landfill
- In folio sheets and reels



www.blauer-engel.de/uz14



CERTIFICATES

- ISO 9001
- ISO 14001
- DIN 6738